

Scuba Cylinders

Specifications

Sales Part Number	Service Pressure		Capacity Air		Outside Diameter		Overall Length		Empty Weight		Min. Internal Volume		Water Weight		Salt Water Buoyancy						Thread Size
															Full		Half		Empty		
															lbs	kg	lbs	kg	lbs	kg	
S006	3000	207	6.1	172.8	3.21	81.41	11.1	282.6	2.5	1.2	54	0.9	1.94	0.88	-1.37	-0.62	-1.14	-0.52	-0.91	-0.41	0.750-14 NPSM
S009	3000	207	8.2	232.2	4.38	111.13	9.3	235.0	4.5	2.0	72	1.2	2.60	1.18	-2.00	-0.91	-1.69	-0.77	-1.39	-0.63	0.750-14 NPSM, M18 x 1.5
S13S	3000	207	13.2	373.8	4.38	111.13	13.1	333.4	6.0	2.7	116	1.9	4.18	1.90	-1.71	-0.78	-1.21	-0.55	-0.72	-0.33	0.750-14 NPSM
S014	2015	139	13.7	388.0	4.38	111.13	16.2	411.1	4.9	2.2	172	2.8	6.20	2.81	0.80	0.36	1.32	0.60	1.83	0.83	0.750-14 NPSM
S019	3000	207	19.9	563.6	4.38	111.13	18.6	471.4	8.2	3.7	175	2.9	6.30	2.86	-1.38	-0.63	-0.64	-0.29	0.11	0.05	0.750-14 NPSM
S027	3000	207	27.6	781.6	5.25	133.35	18.0	457.2	11.5	5.2	242	4.0	8.73	3.96	-1.43	-0.65	-0.39	-0.18	0.65	0.29	0.750-14 NPSM
S030	3000	207	30.0	849.6	4.88	123.83	21.9	555.0	11.6	5.3	263	4.3	9.48	4.30	-1.02	-0.46	0.11	0.05	1.23	0.56	0.750-14 NPSM
S040	3000	207	40.0	1132.8	5.25	133.35	24.6	628.7	15.3	6.9	350	5.7	12.62	5.72	-0.70	-0.32	0.80	0.36	2.30	1.04	0.750-14 NPSM
S050	3000	207	48.4	1370.7	6.89	175.01	19.0	482.6	21.2	9.6	424	6.9	15.29	6.94	-2.27	-1.03	-0.46	-0.21	1.36	0.62	0.750-14 NPSM
S063	3000	207	63.0	1784.2	7.25	184.15	21.9	555.0	26.7	12.1	552	9.0	19.90	9.03	-2.16	-0.98	0.20	0.09	2.56	1.16	0.750-14 NPSM
S072	3000	207	69.6	1971.1	6.89	175.01	26.0	660.4	28.5	12.9	610	10.0	22.00	9.98	-1.39	-0.63	1.23	0.56	3.84	1.74	0.750-14 NPSM
S074	3000	207	74.0	2095.7	7.25	184.15	25.0	636.0	30.6	13.9	648	10.6	23.37	10.60	-1.64	-0.75	1.13	0.51	3.90	1.77	0.750-14 NPSM
S808	3000	207	78.2	2214.6	8.00	203.20	22.9	582.4	35.2	16.0	685	11.2	24.70	11.20	-3.66	-1.66	-0.73	-0.33	2.20	1.00	0.750-14 NPSM, M25 x 2.0
S080	3000	207	77.4	2192.0	7.25	184.15	26.1	661.9	31.4	14.2	678	11.1	24.45	11.09	-1.40	-0.64	1.50	0.68	4.40	2.00	0.750-14 NPSM, M25 x 2.0
S80N (NB80)	3300	228	77.4	2172.0	7.25	184.15	25.8	655.6	35.4	16.1	630	10.3	22.72	10.31	-5.75	-2.61	-2.85	-1.29	0.05	0.02	0.750-14 NPSM
S092	3200	221	89.8	2543.1	8.00	203.20	24.8	629.2	37.5	17.0	750	12.3	27.04	12.27	-3.54	-1.61	-0.17	-0.08	3.20	1.45	0.750-14 NPSM
S100	3300	228	98.8	2798.0	8.00	203.20	26.2	665.7	41.0	18.6	804	13.2	28.99	13.15	-4.35	-1.97	-0.64	-0.29	3.06	1.39	0.750-14 NPSM, M25 x 2.0
S85W	4350	300	83.8	2372.1	7.39	187.71	21.5	545.7	28.5	12.9	540	8.8	19.47	8.83	-5.10	-2.31	-1.90	-0.86	1.26	0.57	0.875-14UNF-2B
S106W	4350	300	105.2	2976.4	7.39	187.71	26.1	661.9	33.8	15.3	678	11.1	24.45	11.09	-4.84	-2.20	-0.90	-0.41	3.10	1.41	0.875-14UNF-2B

3016 Kansas Avenue, Riverside, CA 92507 USA,
 Tel: (909) 684 5110 or (800) 764 0366 Fax: (909) 781 6598

